





Automated FDM 3D Printing Workflow

FDM® 3D printing combined with the PostProcess® BASE™ Automated FDM Support Removal Solution creates a rapid, end-to-end, low-touch additive manufacturing workflow.

- Reduce cycle time
- Increase throughput
- Minimize labor
- Increase yield

Once parts are printed, the removal of support material is accomplished automatically in the enclosed PostProcess BASE system. Volumetric Velocity Dispersion spray technology rinses away support material without the risk of part damage that can occur with manual support removal.





Why Use FDM Technology?



Reliability

FDM 3D printers have a proven record of reliability, uptime, and repeatable performance



Durability

A deep material portfolio for the most demanding 3D printing applications



Service Support

Backed by a worldwide, best-in-class support team with 35+ years of experience

FDM technology offers faster creation and deployment of essential DOD applications compared to traditional manufacturing technologies.

- Drone parts and subassemblies
- Strong, lightweight, ergonomic tooling customized for the user and the application
- On-demand production of spare parts and replacements for obsolete parts



Why use PostProcess BASE?



Proven

Used by numerous DOD branches, contractors, and manufacturers



Consistent

Dependable post-processing results, part after part



High-Performance

Delivers 6X-10X faster results compared to traditional dunk tanks

Real-World Results

Automotive lighting manufacturer J.W. Speaker achieved significant savings with FDM and BASE for 3D printed tooling:

- 98% reduction in post-print drying time (10 minutes with BASE vs. overnight)
- 78% part production time savings using combined FDM process with BASE (9 hrs. vs 1 week)
- \$60K \$75K annual savings (FDM/BASE vs. machining)

Stratasys Direct contract manufacturing services achieved similar results during its BASE evaluation:

- Improved yield (less part breakage, fewer non-conformance reports)
- 40% faster support removal speed vs. ultrasonic
- 67% 75% post-support removal drying time improvement (2-4 hrs. from 8-12 hrs.)

FDM technology + BASE

Learn more about Stratasys FDM Technology.



Learn more about PostProcess BASE.



alphacam GmbH Erlenwiesen 16 D-73614 Schorndorf Tel.: +49 7181 9222-0 info@alphacam.de alphacam austria GmbH Handelskai 92, Gate1 / 2. OG / Top A A-1200 Wien Tel.: +43 1 3619 600-0 info@alphacam.at alphacam swiss GmbH Zürcherstrasse 14 CH-8400 Winterthur Tel.: +41 52 26207-50 info@alphacam.ch



stratasys.com ISO 9001:2015 Certified

TWO PAGER

FDM

